

## RP90R *Plastic Rotary Pump*



With Teflon seal, Ryton vane, PP spout, PP suction tube.  
The outlet can be freely adjusted from 0° to 360°  
Applicable Liquids: acid, alkali, gasoline, diesel, machine oil, water, alcohol, thinner, and other chemical liquids.  
PATENTED IN TAIWAN, CHINA, FRANCE.

- Pump Type: Rotary - Vane
- Flow: 300 ml / Rotation
- Maximum Fluid Temperature: 140°F / 60°C
- Mounting: 2" MNPT Bung Adapter
- Suction Tube Length: 40" Maximum
- Inlet: 1-1/4" O.D.
- Outlet: 1" O.D. Curved Spout
- Component Materials: PPS, TEFLON, VITON
- Maximum Viscosity: 2,000 SSU
- Option: Polyethylene Extension Hose
- Standard Packing: 6pcs/ctn, NW: 16kgs, GW: 17kgs, Cuft: 2.2'

- Made from advanced Non-oxidation and Rust-resistant materials - Stainless Steel and Polyphenylene Sulfide (PPS).
- Ideal for transferring soluble, corrosive, volatile and aggressive chemicals, such as Esters, Alcohols, Alkali, Acids, Hydrocarbons and other fluids are compatible with pump component materials.
- Also suitable for transferring Petroleum based fluids, Transmission Fluid and water based chemicals.
- Supply with 2" bung adapter and 3-piece stainless steel suction tube to fit most 15, 30 and 55 gallon drums.
- Self-priming unit, dispenses approximately 300 ml per stroke

**Part No: RP90R**