



M-3130

30 GPM flowrate for stationary tank applications.

- Weight centering inlet base includes pressure relief and easy strainer access
- Field-replaceable switch and vanes
- Internal auxiliary temperature limiting device motor protection
- Cold weather (XTS) model available

M-3130 SPECIFICATIONS

Flowrate (GPM / LPM)	30 / 114
Voltage	115- or 230-volt AC
Type	Carbon Vane
Duty Cycle (On / Off)	30 min. / 30 min.
Inlet / Outlet Size	1 ¼ in. / 1 in. NPT
Dispensing Hose	12 ft. (3.7m) x 1 in.
Warranty	2 Year Pump
Certifications	LISTED

ORDERING INFORMATION

Model	Part No.	Voltage	Nozzle	Nozzle Holder	Hose	Inlet Mount
M-3130-AD	133220-2	115/230	Auto Diesel	Lockable	12 ft.	Center Base
M-3130-ML	133220-1	115/230	Manual	Lockable	12 ft.	Center Base
M-3130-PO	133220-03	115/230	None	Lockable	None	Center Base
M-3130-PO-XTS	133220-93	115/230	None	Lockable	None	Center Base



M-3130-AD



M-3130-ML



M-3130-PO / M-3130-PO-XTS