

P-120H 12Volt Plastic Herbicide Transfer Pump

SPECIFICATIONS

Applications

Fluids:

Suitable for a wide variety of thin fluid products, including many herbicides and water.

Operating Environment:

Outdoor, year-round with an operating temperature range of -29° to +52°C. Designed for mounting on portable, vented storage tanks.

Pump Housing:

Lightweight, polyester (glass filled). convenient spin collar for easy installation.

Performance

Pump Rate: Up to 45 LPM.
Duty Cycle: 30 min.
Dry Prime: 5.5 ft. (1.7m)
Total head: 25 ft. (7.6m)
Current Draw: 18 amp

Electrical

Input: 12 volt DC
Cord: 15 ft. (4.6m) of 12 gauge
Fuse: 25 amps AGC
Motor: 1900 RPM.

Mechanical Connections

Bung: 2 inch NPT Spin collar for drums
Inlet: 1 inch BSP

Outlet: 1 inch BSP

Ship Weight: 6.8 kg.

PRICE: *



The Plastic Utility Pump uses rotary gear design to produce delivery rates that make fluid transfer a quick and efficient operation. The lightweight plastic housing and convenient carrying handle make this the most portable pump family on the market. Utility is taken seriously with these pumps. Durable plastic components ensure easy maintenance and a wide range of fluid compatibility. Available with 2", 4", or cage mount connections, these pumps are sure to satisfy many needs. Recirculation is available on all models with 4" tank connections.