


Chemical Swing Hatch

DATA SHEET

PART N°: SH303 Series

TITLE:	Hatch for top of tanker allowing access to compartments
PURPOSE:	This manhole is for tankers that carry dangerous goods where frequent entry is required, such as for cleaning when changing loads. Manhole complies with UK and USA requirements and drop test approved in Australia. SH303 hatches include an integral emergency vent and has a mounting boss for a pressure vacuum vent.
OPERATION:	Wingnut type clamps are undone (ones closest to hinge first) then cover swings open for access to compartment.
DISMANTLE:	Not recommended
ADJUSTMENT:	None required
MATERIALS:	Cover - Aluminium Coaming - Aluminium, mild steel or stainless steel Seals – Buna Nitrile, Viton A or Teflon
WEIGHT:	12.6kg
VARIANTS:	SH303 -  <ul style="list-style-type: none">Vent seal, Viton (V) or Teflon (T)Main seal - Buna (B), Viton (V)Coaming - Aluminium (A), M/S (M) or S/S (S)Cover - Aluminium (A)
TECHNICAL DATA:	Emergency vent opens at 30kPa Capacity 7450m ³ /hr at 45kPa
ASSOCIATED EQUIPMENT:	SH301 Series hatches SH302 Series hatches SH304 Series hatches

Overall dimensions shown on the drawing overleaf.

