

## GREASE COMPRESSORS AND BUCKET PUMPS

151 102



## HIGH PRESSURE GREASE PUMPS

High pressure steel pumps to be mounted directly onto original grease kegs. Maximum pressure: 350 bar (5,000 psi). Delivery per stroke 2 cc.

Pump equipped with carrying handle, cover with pump adaptor, follower disc and 1,5 m high pressure hose with rigid stem and four-jaw hydraulic connector.

**151 100 High pressure grease pump for 12.5 to 18 kg kegs**

Includes a 310 mm drum cover.

**151 102 High pressure grease pump for 20 kg kegs**

Includes a 330 mm drum cover.

150 000



## BUCKET PUMPS

Bucket pumps include a 16 liter leak proof, all steel oval shaped bucket with carrying handle and foot rest for easy handling and stability.

**150 000 Multipressure grease bucket pump 16 kg**

Heavy duty high capacity grease pump with three alternative lever positions, which can be used under any operating conditions and with all type of lubricants (winter / summer, high or low viscosity grease, oil). Maximum pressure range between 175 to 350 bar (2,500 to 5,000 psi) with a delivery of 20 gr, 15 g or 10 g per stroke depending on the position of the lever chosen. Pump includes 1,5 m high pressure hose with a three-jaw hydraulic connector (PN 715 429).

**320 400 Oil bucket pump 16 liters**

For dispensing high viscosity lubricants. Includes a medium pressure lever action pump (100 cc delivery per stroke) with a 1,5 m rubber hose with shut off valve and 135° angled nozzle.

320 400



157 000

## PEDAL ACTION GREASE PUMP 5 kg


**157 000 Pedal action grease pump**

Pedal action heavy-duty grease pump. Spring primed follower plate and cast iron pump mechanism ensures that the pump can be used even with extremely viscous grease. Maximum pressure: 500 bar (7,150 psi).

Delivery per pedal stroke: 2 g.

Steel leak proof reservoir, can hold up to 5 kg of grease. Includes air bleeder valve and 2 m high pressure grease hose with a four jaw hydraulic connector with check valve.