

352220

**PNEUMATIC PISTON OIL PUMP, PUMPMASTER 2, PM2 - 2:1
 (KIT COMPONENT)**


PM2 series air operated piston pumps. This is a component for a kit, PUMPMASTER 2, 2:1 ratio pneumatic piston oil pump.

DATOS TÉCNICOS

Air consumption	165 NL/min (5.8 scfm)
Air inlet	1/4" NPSM (F)
Air motor effective diameter	35 mm (1.4 ")
Air motor stroke	75 mm (3 ")
Air pressure operating range	3 - 10 bar (43.5 - 145 psi)
Cycles per minute (aprox.)	175 cycles
Delivery	10 l/min (2.7 gal/min)
Delivery per cycle	15 l (4 gal)
Fluid inlet	3/4" BSP (F)
Fluid inlet type	Ball check
Fluid outlet	3/4" NPSM (F)
Fluids	Transmission fluid, Lubricant oil, Hydraulic oil, Diesel
Maximum free flow delivery (SI)	35 l/min, 9.3 gal/min, 35 l/min
Maximum outlet pressure	20 bar (290 psi)
Noise level	80 dB
Pressure ratio	2:1
Pump mounting	Universal stub pump
Total height	560 mm (22 ")
Tube height	270 mm (10.5 ")
Weight	5 kg (11.1 lb)
Wetted materials	Polyurethane, Acetal, Aluminium, Steel, NBR

DOCUMENTACIÓN
NOMBRE
DESCRIPCIÓN

835810.pdf

Instructions manual 1

[+ INFO](#)

Not available

Not available

CUADRO DE MODELOS

508125

Pump mounting	-
Tube height	-
Total height	-

352220

Pump mounting	Universal stub pump
Tube height	270 mm (10.5 ")
Total height	560 mm (22 ")

544015

Pump mounting	185 kg (400 lb) drums
Tube height	261 mm (10.2 ")
Total height	1221 mm (48.2 ")

532330

Pump mounting	Bulk tote
Tube height	164 mm (6.4 ")
Total height	684 mm (27 ")

551021

Pump mounting	-
Tube height	-
Total height	-

740410

Pump mounting	Universal stub pump
Tube height	450 mm (17.6 ")
Total height	660 mm (26 ")