

363 078 - 363 077

363 051



## OIL CONTROL GUNS

Oil control guns, manufactured in aluminium, with ergonomic grip and trigger to reduce operator hand fatigue. NBR valve with progressive action, for comfortable operation when dispensing products, even with high ratio (10:1) oil pumps. All guns include a ball bearing inlet swivel with large capacity screen filter.

Maximum working pressure: 105 bar (1,500 psi). Maximum delivery: 25 l/min (6.6 US gpm). Fluid inlet thread: 1/2" NPSM (F).

Guns available with a variety of outlets to fit every application.

## MODELS

PART No.	APPLICATION	OUTLET TYPE INCLUDED	NON DRIP NOZZLE INCLUDED
363 082		None	None
363 075	Gear oil	110° rigid swiveling (369 217)	Manual
363 077	ATF , lubricants	Straight flexible (369 200)	Manual
363 078	All types of lubricants	Flexible with 90° outlet, swiveling (369 218)	Semi automatic
363 079	Motor oil	60° rigid (369 215)	Semi automatic

## HIGH DELIVERY OIL CONTROL GUN

**363 051 High delivery oil control gun**

High delivery oil control gun manufactured in aluminium. A double valve mechanism allows small flow deliveries when the trigger is partially open and full flow delivery when the trigger is fully pressed. Lockable trigger and ball bearing inlet swivel. This oil gun includes a 60° angled rigid outlet with semiautomatic non drip nozzle.

Maximum working pressure: 105 bar (1,500 psi). Maximum delivery: up to 45 l/min (11.7 US gpm). Fluid inlet thread: 3/4" BSP (F).