


HOSE END METERS FOR OIL

365 652

365 300

365 710





365 652 High delivery hose end meter

Oval gear hose end meter with electronic digital LCD display for metered delivery of lubricants up to SAE 140. The display is powered by two easily replaceable AAA 1.5 V alkaline batteries. The meter is coupled to a high delivery oil

control gun that incorporates a rugged ball bearing inlet swivel with an inlet filter and 60° rigid outlet with semi automatic non drip nozzle. All hose end meters are supplied with a protective rubber shroud.

Maximum working pressure: 105 bar (1,500 psi). Maximum flow range: up to 25 l/min (6.5 US gpm). Fluid inlet thread: 3/4" BSP (F).



PRESET HOSE END METER

365 300 Preset digital meter

Oval gear hose end meter with preset function. Preset mode dispensing allows hands off operation as the meter automatically shuts off the oil once the preset volume is delivered.

Meter with digital display, works with four easy to replace 1.5 AA alkaline batteries. Includes rigid outlet with non drip nozzle and inlet swivel.



WEIGHTS AND MEASURES APPROVED HOSE END METER

365 710 Weights and Measures approved hose end meter

Oval gear hose end meter with digital display approved by German Weights and Measures aurothority (PTB).

Includes calibration certification, protective shroud, inlet swivel and sight glass. Order outlet accessory separately.



Wellington Head Office: 90 Sydney St, PO Box 38 720 Petone, Wellington, Tel: 64 4 568 4933, Fax: 64 4 568 4789 Email: sales@liquip.co.nz Website: www.liquip.co.nz

See pag 63 for accessories.