

365 675 415 002





365 675 Hose end meter for other service fluids

Oval gear hose end meter with electronic digital LCD display for measured delivery of fluids such as windshield washer, glycol solution and other water based fluids. Display is powered by two easily replaceable AAA 1.5 V alkaline batteries. The meter has two separate displays in litres, a resettable 4 digit batch display and a permanent totalizer. Meters are factory calibrated and they can easily be re-calibrated in the field for increased accuracy. Meter can measure in litres, quarts, pints and US gallons.

The meter is coupled to fluid control gun (PN 186 300).

Maximum working pressure: 40 bar (570 psi). Flow range: 5 to 15 l/min (1.3 to 4 US gpm). Fluid inlet thread: 1/2" BSP (F).



HOSE END METER FOR GREASE

High pressure oval gear meter with electronical digital LCD display for accurate greasing. The display is powered by two easy to replace AAA 1.5 V alkaline batteries and shows the amount delivered in grams (up to 9,999 gr) and a permanent totalizer in kilograms (up to 999,999 kg). Includes a batch display reset button. Meters are factory calibrated and they can easily be recalibrated in the field for increased accuracy. The meter is coupled to a high pressure grease control gun with ergonomic body and trigger to reduce operator hand fatigue.

Maximum working pressure 500 bar (7,150 psi).

415 002 High pressure grease hose end meter Includes:

Double steel braid reinforce rubber hose (400 mm) with hydraulic grease connector and Z swivel.

415 000 High pressure grease hose end meter Includes:

Z-swivel, with no outlet accessories.



Wellington Head Office: 90 Sydney St, PO Box 38 720 Petone, Wellington, Tel: 64 4 568 4933, Fax: 64 4 568 4789 Email: sales@liquip.co.nz Website: www.liquip.co.nz