

AdBlue®/DEF ACCESSORIES

366 010

AdBlue®/DEF ELECTRONIC LINE METERS



366 010 AdBlue®/DEF oval gear meter

Oval gear meter manufactured in PVC, stainless steel and acetal for AdBlue®/DEF. Digital display, works with two AAA alkaline batteries. Inlet/outlet thread 1/2" BSP (F). Flow rate: 1-50 l/min.

366 760 AdBlue®/DEF meter, 1" BSP (MM)

Digital line meters provided with metering chamber with turbine system, electronic display, reset button, partial metering function (99.999 l), resettable totalizer (999.999), calibration function. Flow rate: 8-110 l/min. Max. pressure: 10 bar. Precision: +/- 1%. Power supply: 2 x 1,5 V batteries.

366 976 AdBlue®/DEF meter with a stainless steel female adaptor, 1" BSP (FM)

366 761 AdBlue®/DEF meter with a 2 stainless steel female adaptors, 1" BSP (FF)

689 055 Polypropylene thread adaptor, 1" BSP (FF)

945 708 Stainless steel thread adaptor, 1" BSP (FF)

569 000

AdBlue®/DEF NOZZLES



AdBlue®/DEF nozzles with stainless steel and thermoplastic versions available. Depending on the model they can be manual or automatic, with spike or thread connection.

361 003.370 Manual (thermoplastic), 90 l/min, 1" BSP (F) inlet thread

361 002.370 Manual (thermoplastic), 90 l/min, Ø 25 mm inlet thread

361 001.370 Manual (thermoplastic), 90 l/min, Ø 19 mm inlet thread

569 000 Automatic (stainless steel), 45 l/min, Ø 19 mm inlet thread

569 001 Automatic (stainless steel/polypropylene), 45 l/min, Ø 19 mm inlet thread

930 507

AdBlue®/DEF HOSES



EPDM HOSES

Service EPDM hoses for AdBlue®/DEF transferring or suction, sold in bulk (minimum 1 m).

930 507, Ø 19 mm / 1 m EPDM hose

930 505, Ø 13 mm / 1 m EPDM hose

PVC HOSES

Transparent suction hoses made of reinforced PVC for AdBlue®/DEF transferring.

689 030, 2 m x PVC suction hose Ø 25 mm

With swaged terminals and foot valve 689 042, 1" BSP (M).

689 031, 4 m x PVC suction hose Ø 25 mm

With swaged terminals and foot valve 689 042, 1" BSP (M).

932 025, 1 m hose PVC Ø 25 mm in bulk

(Minimum 1 m).

AdBlue®/DEF ACCESSORIES



689 041



560 901



360 137

689 042 Polypropylene foot valve with filter. 1" BSP (F)

560 903 Polypropylene foot valve. 1" BSP (F)

689 041 Polypropylene filter for suction hose, Ø 25 mm hose barb connection

689 047 Polypropylene hose tail connection kits, Ø 19 mm. 1" BSP (M), with connection clamps

689 048 Polypropylene hose tail connection kits, Ø 25 mm. 1" BSP (M), with connection clamps

560 901 CSC quick coupling, Ø 19 mm hose barb connection

560 902 Suction tube for CSC connection. With 2" BSP (M) connection

560 906 Suction tube for CSC connection. With 2" TRISURE connection



Wellington Head Office: 90 Sydney St, PO Box 38 720
Petone, Wellington, Tel: 64 4 568 4933, Fax: 64 4 568 4789
Email: sales@liquip.co.nz Website: www.liquip.co.nz